



12 Gauge Shotgun Ammunition

www.polyshok.com

Polyshok delivers more stopping power, with less potential for collateral damage than any other shotgun, rifle or pistol ammunition ever made. Guaranteed!



Specifications:

- Standard 12 ga. 2 ¾" shell
- Weight: 540 gr. Ballistic Polymer Composite Projectile
- Average Velocity: 1045 FPS (18 in. barrel 10 feet from muzzle)
- Maximum Breech Pressure: Less than 9,500 psi
- Low Recoil: Half the recoil of 9 pellet load of 00 Buckshot
- Optimum Range: Up to 50 yd.
- Trajectory: 25 yd. = + ½"; 50 yd. = 0"; 100 yd. = - 8 ½"
- Accuracy: 4" or less average 5 shot group (Center to center @ 50 yd. - 18 in. smoothbore barrel)
- Barrel Maintenance: Recommended cleaning schedule every 100 rd. (To maintain optimum accuracy)
- Maximum Flight Distance (from level shoulder fired shot): 175 yd. (Compare to M16 Carbine @ 550 yd.)
- Optimum Operational Temperature: 0° - 160° F (temperature of the round itself at firing)
- Meets International Wound Ballistics Association's terminal performance criteria: Permanent wound cavity eight inches deep and five inches in diameter for both bare and heavy denim clad 10% ordnance gelatin

Features:

- Proven street results with one-shot stops and no exit wound
- Available only to Law Enforcement, Military and Licensed Security
- Transforms 12 gauge shotgun into most effective and safest weapon available for use in the urban environment
- Provides stopping power equal to a 12 gauge slug
- Virtually eliminates potential for collateral damage due to over penetration, stray pellets or missed shots
- Door breaching capability
- Polyshok has a very informative website located at www.polyshok.com. Video clips from a live-fire demo, references, training

Contact Us ▶▶

Jim Middleton
 2702 Woodmere Drive
 Panama City, FL 32405
 (888) 820-2010 Toll Free
 (850) 763-3619 Fax
 (850) 625-9412 Cell
jmittleton@polyshok.com